



EXISAFE-3T




EXISAFE-3T is powerful surface-mounted LED emergency luminaire for spaces where ceiling height exceeds 10 m. EXISAFE-3T/120, on the other hand, is designed for ceiling heights of under 10 m. Light fitting delivers a wide, rotationally symmetrical light pattern. IP55 rated luminaire is also well suited for emergency lighting in humid locations. It has an ABS plastic body. The standard colour for the plastic parts is white (RAL9016).

There is a flush-mounting frame (UPK-EXISAFE) available for the recessed installation of the luminaire. A hole with a 165 mm diameter is used for the recessed installation.


Typical applications include production and warehouse facilities, car parks, sports halls and indoor ice rinks, lobbies and other public spaces where effective emergency lighting is needed.



Premises with the ceiling height below 10 m, (with 120-degree lens).



Valaisimien asennusväli n. 11 m asennuskorkeudella 3 m.



Premises with the ceiling height above 10 m, (with 30-degree lens)

EXIOT LUMINAIRES

| TYPE | ELECTRICAL NO. (FI) | VOLTAGE | POWER INPUT | LIGHT SOURCE | IP CLASS | MOUNTING | BATTERY |
|------------------|---------------------|---------|-------------|--------------|----------|--------------------------|------------------------|
| EXISAFE-3T/W | 4129222 | 230 V | 12W | LED | 55 | MMJ 3×1,5mm ² | Li-ion 7,4V / 1300 mAh |
| EXISAFE-3T/W/120 | 4129223 | 230 V | 12W | LED | 55 | MMJ 3×1,5mm ² | Li-ion 7,4V / 1300 mAh |

ADDRESSABLE LUMINAIRES

| TYPE | ELECTRICAL NO. (FI) | VOLTAGE | POWER INPUT | LIGHT SOURCE | IP CLASS | MOUNTING | BATTERY |
|------------------|---------------------|---------|-------------|--------------|----------|------------------------------------|------------------------|
| EXISAFE-3T/C | 4228641 | 65V DC | 12W | LED | 55 | -o-KLMA 2×0,8+0,8 | Li-ion 7,4V/ 1200 mAh |
| EXISAFE-3T/P | 4228640 | 65V DC | 2W | LED | 55 | FRHF – JE-H(St) H..Bd 2×0,8+0,8 | Central battery system |
| EXISAFE-3T/C/120 | 4228642 | 65V DC | 12W | LED | 55 | -o-KLMA 2×0,8+0,8 | Li-ion 7,4V/ 1200 mAh |
| EXISAFE-3T/P/120 | 4228645 | 65V DC | 12W | LED | 55 | FRHF – JE-H(St) H..Bd 2×0,8+0,8 | Central battery system |

24V AND 230V LUMINAIRES

| TYPE | ELECTRICAL NO. (FI) | VOLTAGE | POWER INPUT | LIGHT SOURCE | IP CLASS | MOUNTING | BATTERY |
|-------------------|---------------------|------------|-------------|--------------|----------|-------------------------|------------------------|
| EXISAFE-3T | 4228638 | 230V AC/DC | 12W | LED | 55 | -o-3×2,5mm ² | Central battery system |
| EXISAFE-3T/24 | 4228643 | 24V DC | 12W | LED | 55 | -o-3×2,5mm ² | Central battery system |
| EXISAFE-3T/120 | 4228639 | 230V AC/DC | 12W | LED | 55 | -o-3×2,5mm ² | Central battery system |
| EXISAFE-3T/24/120 | 4228644 | 24V DC | 12W | LED | 55 | -o-3×2,5mm ² | Central battery system |