





ACUTA is well suited for industrial buildings, warehouses and halls. Rugged construction, IP66 and IK10 ratings and automatically adjustable lighting properties deliver excellent performance and ensure a long service life for the luminaire. Motion detection and dark sensor technology maximises energy savings in extensive projects that set high requirements for lighting.

LIGHTING INFORMATION

- Colour rendering index: RA ≥ 80
- Light source cover: Polycarbonate
- Casing: IP66
- Impact resistance: IK10
- Supply voltage: 220–240 VAC
- Frequency: 50–60 Hz
- PF: > 0.92
- THD: <10%
- Overvoltage protection: 4 kV L/N-Ground (Optional 10 kV)
- Connection: Internal terminal strip
- Dimming/Control: ON/OFF, 1–10 V, DALI*, presence sensor
- Colour: Black
- Frame material: Aluminium
- Warranty: 5 years
- Protection category: I
- Installation: Suspension



**ACUTA**

ELECTRICAL NO. (FI)	PRODUCT CODE	TYPE	VOLTAGE	POWER INPUT	LIGHT SOURCE	IP CLASS	MOUNTING
4325201	ACUTA-100-90	High-bay luminaire	230V	100W	LED	65	Surface mounting
4325202	ACUTA-150-90	High-bay luminaire	230V	150W	LED	65	Surface mounting
4325203	ACUTA-200-90	High-bay luminaire	230V	200W	LED	65	Surface mounting
4325206	ACUTA-DA-100-90	High-bay luminaire	230V	100W	LED	65	Surface mounting
4325207	ACUTA-DA-150-90	High-bay luminaire	230V	150W	LED	65	Surface mounting
4325208	ACUTA-DA-200-90	High-bay luminaire	230V	200W	LED	65	Surface mounting
4325211	ACUTA-DASN-100-90	High-bay luminaire	230V	100W	LED	65	Surface mounting
4325212	ACUTA-DASN-150-90	High-bay luminaire	230V	150W	LED	65	Surface mounting
4325213	ACUTA-DASN-200-90	High-bay luminaire	230V	200W	LED	65	Surface mounting