




ALEXI is a series of high-quality, sturdy guide luminaires with an aluminium body. Typical applications include office and business premises, day-care centres, schools, hospitals, health centres and sports halls. Luminaire offers even light distribution as well as good contrast and illumination. Sign is made of acrylic.

There are two viewing distances available in the series: 45 m and 60 m. Luminaire can be wall or ceiling mounted. The series includes light fittings with a downlight function.

Brackets are made of ABS plastic, and the luminaire is IP44 rated. Guide luminaire can be wall or ceiling mounted. Available in one and two-sided models.



EXIOT LUMINAIRES

TYPE	ELECTRICAL NO. (FI)	VOLTAGE	POWER INPUT	LIGHT SOURCE	IP CLASS	RANGE	MOUNTING	BATTERY
ALEXI-2W-A	4129302	230 V	2 W	LED	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-2W-O	4129303	230 V	2.4 W	LED	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-2W-V	4129304	230 V	2.8 W	LED	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-2W/D-A	4129311	230 V	4 W	LED+downlight	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-2W/D-O	4129312	230 V	4.8 W	LED+downlight	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-2W/D-V	4129313	230 V	5.6 W	LED+downlight	44	45 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 600 mAh
ALEXI-3W-A	4129305	230 V	2 W	LED	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh
ALEXI-3W-O	4129306	230 V	2.4 W	LED	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh
ALEXI-3W-V	4129307	230 V	2.8 W	LED	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh
ALEXI-3W/D-A	4129314	230 V	4 W	LED+downlight	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh
ALEXI-3W/D-O	4129315	230 V	4.8 W	LED+downlight	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh
ALEXI-3W/D-V	4129316	230 V	5.6 W	LED+downlight	44	60 m	MMJ 3x1,5mm2	Li-Ion 7,4 V / 1200 mAh



ADDRESSABLE LUMINAIRES

TYPE	ELECTRICAL NO. (FI)	VOLTAGE	POWER INPUT	LIGHT SOURCE	IP CLASS	RANGE	MOUNTING	BATTERY
ALEXI-2C-A	4129284	65 V DC	2 W	LED	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh
ALEXI-2C-O	4129285	65 V DC	2.4 W	LED	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh
ALEXI-2C-V	4129286	65 V DC	2.8 W	LED	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh
ALEXI-2C/D-A	4129293	65 V DC	4 W	LED+downlight	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh
ALEXI-2C/D-O	4129294	65 V DC	4.8 W	LED+downlight	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh
ALEXI-2C/D-V	4129295	65 V DC	5.6 W	LED+downlight	44	45 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 600 mAh

ALEXI-3C-A	4129287	65 V DC	2 W	LED	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh
ALEXI-3C-O	4129288	65 V DC	2.4 W	LED	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh
ALEXI-3C-V	4129289	65 V DC	2.8 W	LED	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh
ALEXI-3C/D-A	4129296	65 V DC	4 W	LED+downlight	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh
ALEXI-3C/D-O	4129297	65 V DC	4.8 W	LED+downlight	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh
ALEXI-3C/D-V	4129298	65 V DC	5.6 W	LED+downlight	44	60 m	KLMA 2×0,8+0,8	Li-Ion 7,4 V / 1200 mAh

230V LUMINAIRES

TYPE	ELECTRICAL NO. (FI)	VOLTAGE	POWER INPUT	LIGHT SOURCE	IP CLASS	RANGE	MOUNTING	BATTERY
ALEXI-2-A	4129266	230 V	2 W	LED	44	45 m	-o- 3×2,5mm ²	Central battery system
ALEXI-2-O	4129267	230 V	2.4 W	LED	44	45 m	-o- 3×2,5mm ²	Central battery system
ALEXI-2-V	4129268	230 V	2.8 W	LED	44	45 m	-o- 3×2,5mm ²	Central battery system
ALEXI-2D-A	4129275	230 V	4 W	LED+downlight	44	45 m	-o- 3×2,5mm ²	Central battery system
ALEXI-2D-O	4129276	230 V	4.8 W	LED+downlight	44	45 m	-o- 3×2,5mm ²	Central battery system
ALEXI-2D-V	4129277	230 V	5.6 W	LED+downlight	44	45 m	-o- 3×2,5mm ²	Central battery system

ALEXI-3-A	4129269	230 V	2 W	LED	44	60 m	-o- 3×2,5mm ²	Central battery system
ALEXI-3-O	4129270	230 V	2.4 W	LED	44	60 m	-o- 3×2,5mm ²	Central battery system
ALEXI-3-V	4129271	230 V	2.8 W	LED	44	60 m	-o- 3×2,5mm ²	Central battery system
ALEXI-3D-A	4129278	230 V	4 W	230 V	44	60 m	-o- 3×2,5mm ²	Central battery system
ALEXI-3D-O	4129279	230 V	4.8 W	230 V	44	60 m	-o- 3×2,5mm ²	Central battery system
ALEXI-3D-V	4129280	230 V	5.6 W	230 V	44	60 m	-o- 3×2,5mm ²	Central battery system